

Model 650-SP0

Technical Data

The KVK model 650-SP0 is an optimal on-farm solution for individual treatments, which will secure a simple, easy and reliable handling and operation. The chute is developed and designed to provide high comfort for the hoof trimmer and livestock during trimming. The 650-SP0 is designed to perform hoof trimming on livestock between 200-900 kg.

The 650-SP0 hoof trimming chute is CE approved and thereby comply with the requirements of the Machine Directive.

A standard model 650-SP0 includes the following:

Front gate open/close	Manual
Back door open/close	Manual
Double belly band	Electrical
Lifting/lowering of the chute	Manual
Leg winch all 4 legs	Manual
Adjustable hoof support plate In/out right/left	Manual
Individual working height	5 individual fixed setting for height
Hot-dip Galvanized	Yes
Transport wheels	2 pcs
Gallow with a socket	Yes
Knives holders	2 pcs
Cup holder	1 pcs
Hot air gun holder	Optional extra
Rubber floor mat	Yes
Hoof support system	Yes
Socket	2 pcs



General Information

Length x width:	250 x 145 cm
Height:	205 cm
Height, lifted:	240 cm, with 5 individual fixed setting for height
Height on wheels	202-210 cm
Standing length	
Front gate to backdoor	190 cm
Front gate to cross bar	175 cm
Weight:	500 kg
Belly band lifting capacity	Belly band (lift): 650 kg Belly band (hold): 1600 kg
Surface treament	Hot dip galvanized
Livestock, optimal weight	200-900 kg

Electrical System

Electrical Motor	1,1 kW
Electrical requirements	3x400 V / 1 x230 V

